

Applications

Quiet Tread was designed to reduce noise commonly associated with normal foot traffic on checker plate / diamond plate metal stairs. For new or existing applications. A solution to solve loud noise created by vibration from normal foot traffic. Making steel stairs as quiet as concrete pan filled stairs.

Important Note: Quiet Tread must be attached to a smooth, clean, dry surface. Each edge of Quiet Tread 1-2 inches away from obstructions, bends, and welds. This is to guarantee the best result and most coverage for absorbing the most vibration. The product must be applied completely flat for a lasting adhesive bond.

1. NEW CHECKER PLATE / DIAMOND PLATE METAL STAIRS/LANDINGS

- Product arrives pre-cut to specified dimensions.
- Applied to the underside of the tread and landing plate during stair fabrication.
- Peel and stick application before stairs are primer painted.
- Commonly installed on 14 ga., 12 ga., 10 ga., 1/8" metal plate.
- After install, the stairs are finished with paint for a clean appearance.



2. EXISTING CHECKER PLATE / DIAMOND PLATE METAL STAIRS/ LANDINGS

- Product arrives pre-cut to specified dimensions.
- Applied to the underside of the tread and landing plate on site.
- The stair tread surfaces which will accept Quiet Tread must be thoroughly inspected, prepared and thoroughly cleaned for a lasting bond.
- Peel and stick application.
- Commonly installed on 14 ga., 12 ga., 10 ga., 1/8" metal plate.
- After install, the stairs are finished with paint for a clean appearance.

